


INFASID®-P plus

Pressure infusion system, sterile

Product Information



MEDICAL PRODUCT Class IIa

INFASID®-P plus is a device for the intravenous pressure infusion of medications and solutions
With bacteria-proof air filter
Also suitable for use with infusion pumps (please follow the instruction manual for the pump system used)

To be used in cases of

- Intravenous administration of medications and solutions into the bloodstream using intravenous catheters or intravenous cannula.

It should not be used

- For blood transfusions
- For the infusion of highly viscous media
- in patients who are sensitive to any of the materials used

PRODUCT DESCRIPTION

Material composition	Protective caps	Polyethylene, PTFE (PE)
	Spike, vented	Acrylonitrile butadiene styrene (ABS)
	Ventilation filter with cap	Polypropylene, PTFE (PP)
	Drip chamber	Polyvinyl chloride (PVC)
	Liquid filter (15 µm)	ABS + nylon
	Hose	Polyvinyl chloride (PVC)
	Roller clamp	Acrylonitrile butadiene styrene (ABS)
	Luer lock connector (male)	Acrylonitrile butadiene styrene (ABS)

Sterile	Ethylene oxide	(EO)
Stability	5 years	
Storage	+5°C to +35°C, in a dry place, away from sunlight	

Disposable product
Not reusable
Free from natural rubber latex
Contains DEHP and PHT
Pyrogen-free

Infusion pressure max. 200 [kPa]
Drops/ml 20 \approx 1 g \pm 0.1 g
Liquid filter 15 μ l

ORDER INFORMATION

REF	PZN (pharmaceutical registration number)	Hose length [cm]	Feature	Units [PCS]
NDCT10	01282070	150	-	100
NDCT40	01884047	190	-	100
NDCT60	09312468	190	Non-return valve	100

MANUFACTURER INFORMATION

Wenzhou K.L.F Medical Plastics Co., Ltd
No. 29 Gangqiang Road, Airport New Area,
Yongxing Street, Longwan District,
325000 Wenzhou, Zhejiang,
P.R. CHINA

IMPORTER

Clinipharma s.r.o.
Viklefova 1795/10
Žižkov, 13000 Praha 3
Czech Republic